Samsung Confidential

Product Information

DATE : 15, Sep, 2011

SAMSUNG TFT-LCD

MODEL : **LTI460HN01**

The Information Described in this Specification is Preliminary and can be changed without prior notice

APPROVED BY	DATE	PREPARED BY	DATE
Jeong-Min Heo	15, Sep,2011	**Chang-Hee Hong**	15,Sep,2011

Application Engineering Part, LCD Division

Samsung Electronics Co . , LTD.

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	1 /29

Contents

Samsung Confidential

| MODEL | LTI460HN01 | Doc. No | 05-000-G-110915 | Page | 2 /29 |

* Revision History

Date	Rev. No	Page	Summary
15, Sep, 2011	000	all	First issued

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	3 /29

General Description

Description

LTI460HN01 is a color active matrix liquid crystal display (LCD) that uses amorphous silicon TFT(Thin Film Transistor) as switching components. This model is composed of a TFT LCD panel, a driver circuit and a backlight unit. The resolution of a 46" is 1920 x 1,080 and this model can display up to 16.7M colors with wide viewing angle of 89° or higher in all directions. This panel is intended to support applications to provide a excellent performance for Flat Panel Display such as Home-alone Multimedia TFT-LCD TV, Display terminals for AV application products, and Digital Information Display (DID).

Features

- RoHS compliance (Pb-free)
- High contrast ratio, High luminance
- SPVA(Super Patterned Vertical Align) mode
- Wide viewing angle (±178°)
- FHD (1920 x 1080 pixels) resolution (16:9)
- Low power consumption
- Direct LED Backlight (640ea)
- DE(Data Enable) mode
- 2ch LVDS (Low Voltage Differential Signaling) interface
- High Tni (85 ℃) Liquid crystal
- Super Narrow Bezel

General Information

Items	Specification		Unit	Note
Module Size	1023.98(W$_{TYP}$) x 578.57(H$_{TYP}$)		mm	±1.0mm
	39.6(D$_{MAX}$)			
Weight	15,000(Max)		g	
Pixel Pitch	0.53025(H) x 0.53025(V)		mm	
Active Display Area	1018.08(H) x 572.67(V)		mm	
Surface Treatment	Haze 44% , Anti-Glare			
Display Colors	8 bit - 16.7M		colors	
Number of Pixels	1920 x 1,080		pixel	16 : 9
Pixel Arrangement	RGB vertical stripe			
Display Mode	Normally Black			
Luminance of White	700 (Typ.)		cd/m^2	

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	4 /29

1. Absolute Maximum Ratings

If the condition exceeds maximum ratings, it can cause malfunction or unrecoverable damage to the device.

1.1 Environmental absolute Maximum Ratings

Item		Symbol	Min.	Max.	Unit	Note
Power Supply Voltage		V_{DD}	GND-0.5	13.2	V	(1)
Storage temperature		T_{STG}	-20	65	℃	(2)
Glass surface temperature (Operation)	Center	T_{CENTER}	0	50	℃	(2),(3)
	T. Uniformity	$\triangle T$	-	10	℃	

1.2 LED Unit absolute Maximum Ratings

Item	Symbol	Max.	Unit	Note
Operating Temperature Range	Top	-30 ~ 85	℃	-
Storage Temperature Range	TSTG	-40 ~ 100	℃	-
Junction Temperature	Tj	125	℃	-
Forward Current	If	180	mA	@LED Module (160 LEDs) 10% Duty
	Ifp	300	mA	
Forward Voltage	Vf	149.6	V	@LED Module (160LEDs) 25℃
Thermal Resistance, Junction to PCB	Rth,JS	35	K/W	Junction to solder

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	5 /29

Note (1) Ta= 25 ± 2 °C
        (2) Temperature and relative humidity range are shown in the figure below.
            a. 90 % RH Max. (Ta ≤ 39 °C)
            b. Relative Humidity is 90% or less. (Ta > 39 °C)
            c. No condensation

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	6 /29

2. Application information for DID (Digital Information Display)

A long-term display like DID application may cause uneven display including image retention.
To optimize module's lifetime and function, several operating usages are required.

 1. Normal operating condition
   - Temperature: 20 ± 15℃
   - Humidity: 55 ± 20 %
   - Display pattern: moving picture or regular switchover display
 Note) Long-term static information image may cause uneven display.

 2. Operating usages under abnormal operating condition. Note (1)
   a. Ambient condition
    - Well-ventilated place is recommended to set up DID system.
   b. Power off and screen saver
    - Periodical power-off or screen saver is needed after long-term static display. Note (2)

 3. Operating usages to protect uneven display due to long-term static information display
   a. Suitable operating time for E-DID : under 20 hours a day.
   b. Periodical display contents change from static image to moving picture.
    - Liquid crystal refresh time is required.
   c. Periodical background color and character (image) color change
    - Use different colors for background and character (image), respectively.
    - Change colors periodically.
   d. Avoid combination of background and character with large different luminance.

 Note (1) Abnormal condition means every operating condition except normal operating condition.
 Note (2) Moving picture or black pattern is strongly recommended for screen saver.

 4. Lifetime in this spec is guaranteed only when DID is used under right operating usages.

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	7 /29

Samsung Confidential

3. Optical Characteristics

The optical characteristics should be measured in a dark room or equivalent.
Measuring equipment : TOPCON BM-7,SPECTRORADIOMETER SR-3

$(Ta = 25 \pm 2°C, V_{DD} = 12V, f_V = 60Hz, f_{DCLK} = 74.25 MHz)$

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Contrast Ratio (Center of screen)		C/R		2500	3500	-		(3) SR-3
Response Time	G-to-G	Tg		-	8	15	msec	(5) BM-7
Luminance of White (Center of screen)		Y_L	Normal $\theta L,R=0$ $\theta U,D=0$ Viewing Angle	600	700	-	cd/m²	(6) SR-3
Color Chromaticity (CIE 1931)	Red	Rx		TYP. -0.03	0.646	TYP. +0.03		(7),(8) SR-3
		Ry			0.335			
	Green	Gx			0.310			
		Gy			0.597			
	Blue	Bx			0.151			
		By			0.068			
	White	Wx			0.280			
		Wy			0.290			
Color Gamut		-		-	72	-	%	(7) SR-3
Color Temperature		-		8000	10000	-	K	(7) SR-3
Viewing Angle	Hor.	θ_L	C/R≥10	75	89	-	Degree	(8) SR-3
		θ_R		75	89	-		
	Ver.	θ_U		75	89	-		
		θ_D		75	89	-		
Brightness Uniformity (9 Points)		B_{uni}		-	-	25	%	(4) SR-3

Note (1) Test Equipment Setup

The measurement should be executed in a stable, windless and dark room between 40min and 60min after lighting the backlight at the given temperature for stabilization of the backlight. This should be measured in the center of screen.

Environment condition : Ta = 25 ± 2 °C

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	8 /29

Samsung Confidential

Photo detector	Field
SR-3	1°
BM-7	2°

Photo detector

Field

SR-3 ：50㎝
BM-7 ：50㎝

TFT - LCD Module

LCD Panel

The center of the screen

Note (2) Definition of test point

320　　　960　　　1600

180　⑨　　⑧　　⑦

Active Area

540　⑥　　⑤　　④

◯ Test Point

900　③　　②　　①

Note (3) Definition of Contrast Ratio (C/R)
: Ratio of gray max (Gmax) & gray min (Gmin) at the center point ⑤ of the panel

$$C/R = \frac{G\max}{G\min}$$

Gmax : Luminance with all pixels white
Gmin : Luminance with all pixels black

Note (4) Definition of 9 points brightness uniformity

$$Buni = 100 * \frac{(B\max - B\min)}{B\max}$$

Bmax : Maximum brightness
Bmin : Minimum brightness

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	9 /29

Samsung Confidential

Note (5) Definition of Response time : Average response time of all Gray to Gray

Display data	Low Gray	High Gray	Low Gray

Optical Instruments Response

T_R T_F

100%
90%

10%
0%

TIME

Note (6) Definition of Luminance of White : Luminance of white at center point ⑤

Note (7) Definition of Color Chromaticity (CIE 1931)
        Color coordinate of Red, Green, Blue & White at center point ⑤

Note (8) Definition of Viewing Angle
        : Viewing angle range (C/R ≥ 10)

Θ_U

Θ_R

Θ_L

Θ_D

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	10 /29

4. Electrical Characteristics

4.1 TFT LCD Module

The connector for display data & timing signal should be connected.

Ta = 25°C ± 2 °C

| Item		Symbol	Min.	Typ.	Max.	Unit	Note
Voltage of Power Supply		V_{DD}	10.8	12.0	13.2	V	(1)
Current of Power Supply	(a) Black	I_{DD}	-	0.5	0.6	A	(2),(3)
	(b) White		-	1.1	1.2	A	
	(c) Sub-V-Stripe		-	1.1	1.2	A	
Vsync Frequency		f_V	-	60	-	Hz	
Hsync Frequency		f_H	-	67.5	-	kHz	
Main Frequency		f_{DCLK}	-	148.5	-	MHz	
Rush Current		I_{RUSH}	-	-	7.0	A	(4)

Note (1) The ripple voltage should be controlled under 10% of V_{DD}.

(2) f_V = 60Hz, f_{DCLK} = 74.25 MHz, V_{DD} = 12.0V, DC Current.

(3) Power dissipation check pattern (LCD Module only)

a) Black Pattern   b) White Pattern   c) Sub -v- Stripe

(4) Measurement Conditions

T_{RUSH}=470μs

Rush Current I_{RUSH} can be measured when T_{RUSH}. is 470μs.

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	11 /29

4.2 Back Light Unit

The backlight unit contains 640LEDs.

Ta=25 ± 2°C

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Operating Life Time	Hr	50,000	-	-	Hour	(1)

Note (1) It is defined as the time to take until the brightness reduces to 50% of its original value.

[Operating condition : Ta = 25±2℃]

Control board

LCD Module

Converter

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	12 /29

Samsung Confidential

4.3 LED Drive DC-DC Converter

Items	Symbol	Conditions	Specifications			Unit	Note
			Min.	Typ.	Max.		
Input Voltage	Vin	-	22	24	26	V	Ta=25±2 °C
Input Current	Iin	Vin = 24.0V dim =Max	-	-	6.33	Adc	Initial turn on
Output Current	I_{LED}	Vin = 24.0V dim =Max	46.5	50	53.5	mArms	After 1 hour Warm-up
Operating frequency	f_{op}	V_{in}=22.0~26.0V dim=max	117	127	137	kHz	
Backlight On/Off	ON	Vin = 24.0V	2.4	-	5.25	V	
	OFF	Vin = 24.0V	0	-	0.8	V	
analog Dimming control	Vdim	Vin=22.0~26.0V	0	-	3.3	V	
	Iout	Vin=22.0~26.0V Vdim=3.3V	46.5	50	53.5	mA	
		Vin=22.0~26.0V Vdim=0V	6.5	9.5	12.5	mA	

Note (1) Power Consumption is measured at 700[cd/m2] of luminance condition which is the typical luminance value. Lamp Current is measured at the point before Lamp.

※ Additional Appendix for supply current

Items	Symbol	Conditions	Specifications			Unit
			Min.	Typ.	Max.	
Input Current	IIN_overshoot	VIN=24V, DIM=3.3V (Within 1hr at BLU ON)	-	5.24	5.38	Adc
	IIN_saturation	VIN=24V, DIM=3.3V (After 1hr Aging)	-	5.17	5.31	

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	13 /29

Samsung Confidential

5. Input Terminal Pin Assignment

5.1 Input Signal & Power

Connector : FI-RE51S-HF (JAE)

PIN No.	Description		PIN No.	Description	
1	Vdd (12V)		26		RE[0]P
2	Vdd (12V)		27		RE[1]N
3	Vdd (12V)		28		RE[1]P
4	Vdd (12V)		29		RE[2]N
5	Vdd (12V)		30		RE[2]P
6	No Connection(1)		31	Even LVDS Signal	GND
7	GND		32		RECLK-
8	GND		33		RECLK+
9	GND		34		GND
10	Odd LVDS Signal	RO[0]N	35		RE[3]N
11		RO[0]P	36		RE[3]P
12		RO[1]N	37		No Connection(1)
13		RO[1]P	38		No Connection(1)
14		RO[2]N	39	GND	
15		RO[2]P	40	No Connection (1)	
16		GND	41	No Connection(1)	
17		ROCLK-	42	No Connection (1)	
18		ROCLK+	43	No Connection(1)	
19		GND	44	No Connection (1)	
20		RO[3]N	45	LVDS_SEL (2)	
21		RO[3]P	46	No Connection(1)	
22		No Connection(1)	47	No Connection(1)	
23		No Connection(1)	48	No Connection(1)	
24	GND		49	No Connection (1)	
25	Even LVDS	RE[0]N	50	No Connection(1)	
			51	No Connection (1)	

Note 1) No Connection : These pins are only used for SAMSUNG internal purpose.
Note 2) LVDS OPTION : IF THIS PIN : HIGH (3.3 V) → NORMAL NS LVDS FORMAT
                    OTHERWISE : LOW (GND) OR OPEN(NC) → JEIDA LVDS FORMAT
Sequence : On = V_{DD}(T1) ≥ LVDS Option ≥ Interface Signal(T2)
               OFF = Interface Signal(T3) ≥ LVDS Option ≥ V_{DD}

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	14 /29

Note (3) LVDS Connector

PCB

Pin No. 1   Pin No. 51

#1   #51

#1   #51

Fig. Connector diagram

a. All GND pins should be connected together and also be connected to the LCD's metal chassis.
b. All power input pins should be connected together.
c. All N.C pins should be separated from other signal or power.

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	15 /29

Samsung Confidential

5.2 LED Converter input & output Pin Configuration

22022WR-014B1 (YEONHO)

Pin No.	Pin Configuration(FUNCTION)
1	Vin (24V)
2	Vin (24V)
3	Vin (24V)
4	Vin (24V)
5	Vin (24V)
6	GND
7	GND
8	GND
9	GND
10	GND
11	No connection
12	ENA (Converter on/off Control signal) DC 0 to 0.8V off, DC 2.4 to 5.25V On
13	No connection
14	Internal Dimming control [0V: Min, 3.3V: Max]

Note) Dimming → Pin 13 : DC Voltage, Pin 14 :Open

5.3 LED drive DC-DC converter Power Sequence

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	16 /29

5.4 LVDS Interface
  - LVDS Receiver : Tcon (merged)
  - Data Format (JEIDA & Normal)

Samsung Confidential

Default LVDS Option : JEIDA

	LVDS pin	JEIDA -DATA	VESA -DATA
TxOUT/RxIN0	TxIN/RxOUT0	R2	R0
	TxIN/RxOUT1	R3	R1
	TxIN/RxOUT2	R4	R2
	TxIN/RxOUT3	R5	R3
	TxIN/RxOUT4	R6	R4
	TxIN/RxOUT6	R7	R5
	TxIN/RxOUT7	G2	G0
TxOUT/RxIN1	TxIN/RxOUT8	G3	G1
	TxIN/RxOUT9	G4	G2
	TxIN/RxOUT12	G5	G3
	TxIN/RxOUT13	G6	G4
	TxIN/RxOUT14	G7	G5
	TxIN/RxOUT15	B2	B0
	TxIN/RxOUT18	B3	B1
TxOUT/RxIN2	TxIN/RxOUT19	B4	B2
	TxIN/RxOUT20	B5	B3
	TxIN/RxOUT21	B6	B4
	TxIN/RxOUT22	B7	B5
	TxIN/RxOUT24	HSYNC	HSYNC
	TxIN/RxOUT25	VSYNC	VSYNC
	TxIN/RxOUT26	DEN	DEN
TxOUT/RxIN3	TxIN/RxOUT27	R0	R6
	TxIN/RxOUT5	R1	R7
	TxIN/RxOUT10	G0	G6
	TxIN/RxOUT11	G1	G7
	TxIN/RxOUT16	B0	B6
	TxIN/RxOUT17	B1	B7
	TxIN/RxOUT23	RESERVED	RESERVED

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	17 /29

5.5 Input Signals, Basic Display Colors and Gray Scale of Each Color

COLOR	DISPLAY (8bit)	RED								GREEN								BLUE								GRAY SCALE LEVEL
		R0	R1	R2	R3	R4	R5	R6	R7	G0	G1	G2	G3	G4	G5	G6	G7	B0	B1	B2	B3	B4	B5	B6	B7	
BASIC COLOR	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	-
	GREEN	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	-
	CYAN	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
	RED	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	MAGENTA	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	-
	YELLOW	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	-
	WHITE	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
GRAY SCALE OF RED	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R0
	DARK ↑	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1
		0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R2
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	R3~ R252
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	↓ LIGHT	1	0	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R253
		0	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R254
	RED	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R255
GRAY SCALE OF GREEN	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G0
	DARK ↑	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G1
		0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G2
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	G3~ G252
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	↓ LIGHT	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	0	0	0	0	0	0	0	0	G253
		0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	G254
	GREEN	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	G255
GRAY SCALE OF BLUE	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	B0
	DARK ↑	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	B1
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	B2
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	B3~ B252
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	↓ LIGHT	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	B253
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	B254
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	B255

Note) Definition of Gray :

Rn : Red Gray, Gn : Green Gray, Bn : Blue Gray (n = Gray level)

Input Signal : 0 = Low level voltage, 1 = High level voltage

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	18 /29

6. Interface Timing

6.1 Timing Parameters (DE mode)

Signal	Item	Symbol	Min.	Typ.	Max.	Unit	Note
Clock	Frequency	$1/T_C$	130	148.5	155	MHz	2Pix/clk
Hsync		F_H	50	67.5	75	KHz	-
Vsync		F_V	-	60	-	Hz	-
Vertical Display Term	Active Display Period	T_{VD}	-	1080	-	Lines	-
	Vertical Total	T_V	1090	1125	1380	Lines	-
Horizontal Display Term	Active Display Period	T_{HD}	-	1920	-	Clocks	-
	Horizontal Total	T_H	2090	2200	2350	Clocks	-

Note) This product is DE mode. And, the input of Hsync & Vsync signal
    is necessary on normal operation.
   Test Point : TTL control signal and CLK at LVDS Tx input terminal in system

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	19 /29

Samsung Confidential

6.2 Timing diagrams of interface signal (DE mode)

| MODEL | LTI460HN01 | Doc. No | 05-000-G-110915 | Page | 20 /29 |

6.3 Power ON/OFF Sequence

To prevent a latch-up or DC operation of the LCD Module, the power on/off sequence should be as the diagram below.

0<T1≤30msec
0<T2≤50msec
0<T3≤50msec
1000msec≤T4

1000msec≤T5
(Recommend Value)
100msec≤T6
(Recommend Value)

2.4 V

T1 : V_{DD} rising time from 10% to 90%
T2 : The time from V_{DD} to valid data at power ON.
T3 : The time from valid data off to V_{DD} off at power Off.
T4 : V_{DD} off time for Windows restart
T5 : The time from valid data to B/L enable at power ON.
T6 : The time from valid data off to B/L disable at power Off.

- The supply voltage of the external system for the Module input should be the same as the definition of V_{DD}.
- Apply the lamp voltage within the LCD operation range. When the backlight turns on before the LCD operation or the LCD turns off before the backlight turns off, the display may momentarily show abnormal screen.
- In case of V_{DD} = off level, please keep the level of input signals low or keep a high impedance.
- T4 should be measured after the Module has been fully discharged between power off and on period.
- Interface signal should not be kept at high impedance when the power is on.

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	21 /29

Samsung Confidential

7. Outline Dimension (Front View)

PRELIMINARY

DUTLINE DIMENSION (1023.78)
BEZEL DPEN (1018.28)
ACTIVE AREA (1018.08)
DUTLINE CENTER

ACTIVE AREA (572.67)
BEZEL OPEN (572.87)
OUTLINE DIMENSION (578.37)

SAMSUNG ELECTRONICS

LTI460HN01-V01
OUTLINE DIMENSION

| Model | LTI460HN01 | Doc. No | 05-000-G-110915 | Page | 22 / 29 |

7. Outline Dimension (Rear View)

Model	LTI460HN01	Doc. No	05-000-G-110915	Page	23 / 29

Samsung Confidential

8. PACKING

8.1 CARTON (Internal Package)
(1) Packing Form
Corrugated fiberboard box and corrugated cardboard as shock absorber
(2) Packing Method

8.2 Packing Specification

Item	Specification	Remark
LCD Packing	8ea / (Packing-Pallet Box)	1. 15kg / LCD (8ea) 2. 8.0Kg / Cushion-Pallet (2ea) 3. 10.5 Kg / Packing-Pallet Box (1ea) >. Cushion-Pallet Material : EPS >. Packing-Pallet Box Material : DW4
Pallet	1Box / Pallet	1. Pallet weight = 8kg
Packing Direction	Vertical	
Total Pallet Size	H x V x height	1250mm(H) x 1130mm(V) x 690mm(height)
Total Pallet Weight	154.5kg	Pallet(8kg) + Module(15*8=120kg) + Cushion(8*2=16kg) + Pallet BOX(10.5kg)

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	24 /29

8.3 Packing Storage condition

| ITEM	Unit	Min.	Max.
Storage Temperature	(℃)	5	40
Storage Humidity	(%rH)	35	75
Storage life	12 months		
Storage Condition	- The storage room should provide good ventilation and temperature control. - Products should not be placed on the floor, but on the Pallet away from 　a wall. - Prevent products from direct sunlight, moisture nor water; Be cautious of 　a build up of condensation. - Avoid other hazardous environment while storing goods. - If products delivered or kept in conditions of over the storage period of 3 　months, the recommended temperature or humidity range, 　we recommend you leave them at a temperature of 20℃ and a humidity of 50% for 24 hours.		

8.4 Packing long-term Storage guide

Long –term Storage Process0	More than 3months Storage or Low temp. Delivery/under 5℃ Storage, →On the 20℃ 50%rH Condition，More than 24hrs release.

| MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	25 /29

Samsung Confidential

9. MARKING & OTHERS

A nameplate bearing followed by is affixed to a shipped product at the specified location on each product.

(1) Part number : LTI460HN01
(2) Revision: Three letters
(3) Lot number : X X X X XXX XX X

- Cell Position No. (In the Glass)
- Glass No. (In the one Lot)
- Lot No. (Glass)
- Month
- Year (Note1)
- Product code
- Line

(4) Nameplate Indication

CH cULus LEAD-FREE   SAMSUNG

LTI460HN01

0529   XXXXXXXXXX   XXX

MADE IN KOREA

80mm
40mm

Week code : 05 29
- week
- year

Revision code
Lot number

(5) Packing box attach

DVC : LTI460HN01
TYPE: XXXX
QTY : 8
ZAT53K0003   G1

100mm
165mm

Part number
Box serial number

(6) Others
   1. After service part
     Lamps cannot be replaced because of the narrow bezel structure.

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	26 /29

10. General Precautions

10.1 Handling

(a) When the Module is assembled, it should be attached to the system firmly using all mounting holes. Be careful not to twist and bend the Module.

(b) Because the inverter use high voltage, it should be disconnected from power before it is assembled or disassembled.

(c) Refrain from strong mechanical shock and / or any force to the Module. In addition to damage, this may cause improper operation or damage to the Module and LED back light.

(d) Note that polarizers are very fragile and could be damage easily. Do not press or scratch the surface harder than a HB pencil lead.

(e) Wipe off water droplets or oil immediately. If you leave the droplets for a long time, staining or discoloration may occur.

(f) If the surface of the polarizer is dirty, clean it using absorbent cotton or soft cloth.

(g) Desirable cleaners are water, IPA(Isopropyl Alcohol) or Hexane. Do not use Ketone type materials(ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.

(h) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth . In case of contact with hands, legs or clothes, it must be washed away with soap thoroughly.

(i) Protect the module from Electrostatic discharge. Otherwise the ASIC IC or semiconductor would be damaged.

(j) Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.

(k) Do not disassemble the Module.

(l) Do not disassemble shield case of inverter & LVDS board

(m) Do not connect N.C pins. (Samsung internal use only)

(n) Protection film for polarizer on the Module should be slowly peeled off just before use so that the electrostatic charge can be minimized. Must put on antistatic glove while handling a module

(o) Pins of I/F connector should not be touched directly with bare hands.

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	27 /29

10.2 Storage

(a) Do not leave the Module in high temperature, and high humidity for a long time. It is highly recommended to store the Module with temperature from 0 to 35℃ and relative humidity of less than 70%.

(b) Do not store the TFT-LCD Module in direct sunlight.

(c) The Module should be stored in a dark place. It is prohibited to apply sunlight or fluorescent light in storing.

10.3 Operation

(a) Do not connect or disconnect the Module in the "Power On" condition.

(b) Power supply should always be turned on/off by the "Power on/off sequence"

(c) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference should be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.

(d) The cable between the back light connector and its inverter power supply should be connected directly with a minimized length. A longer cable between the back light and the inverter may cause lower luminance of LED and may require higher startup voltage(Vs).

10.4 Operation Condition Guide

(a) The LCD product should be operated under normal conditions.
  Normal condition is defined as below;
    - Temperature : 20±15℃
    - Humidity : 55±20%
    - Display pattern : continually changing pattern (Not stationary)

(b) If the product will be used in extreme conditions such as high temperature, humidity, display patterns or operation time etc.., It is strongly recommended to contact SEC for Application engineering advice. Otherwise, its reliability and function may not be guaranteed. Extreme conditions are commonly found at Airports, Transit Stations, Banks, Stock market, and Controlling systems.

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	28 /29

Samsung Confidential

10.5 Others

(a) Ultra-violet ray filter is necessary for outdoor operation.

(b) Avoid condensation of water. It may result in improper operation or disconnection of electrode.

(c) Do not exceed the absolute maximum rating value. (supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on)
Otherwise the Module may be damaged.

(d) If the Module keeps displaying the same pattern for a long period of time, the image may be "sticked" to the screen.
To avoid image sticking, it is recommended to use a screen saver.

(e) This Module has its circuitry PCB's on the rear side and should be handled carefully in order not to be stressed.

(f) Please contact SEC in advance when you display the same pattern for a long time.

MODEL	LTI460HN01	Doc. No	05-000-G-110915	Page	29 /29